



| VERMEER®* Drill Rig [Type] | Thread type [-] | Drill pipe type [-] | Type Upset [-] | Grade [-] | Size: Outside Diameter [in.] mm | Wall Thickness [in.] mm | Effective length [ft] mm | Tool joint OD [in.] mm | Tool joint ID [in.] mm | Pin length [in.] mm | Max. MUT [ft-lb] Nm | Min. bending radius [ft] m | Max. % bend per drill pipe [%] / ° | Part Number |
|---|--------------------|------------------------|-------------------|--------------|---------------------------------------|----------------------------|-----------------------------|---------------------------|---------------------------|------------------------|------------------------|-------------------------------|---------------------------------------|-------------|
| D6x6 | FS1#200 | one piece forged | IEU | Z140 | 1,49 37,8 | 0,216 5,5 | 6 1.829 | 1,890 48,0 | 0,748 19,0 | 1,990 50,5 | 899 1.219 | 114 35 | 9,9 5,7° | PP19001 |
| D7X11 / D7x- D10X15 S3 | FS1#200 | one piece forged | IEU | Z140 | 1,66 42,2 | 0,256 6,5 | 6 1.829 | 1,890 48,0 | 0,748 19,0 | 1,996 50,7 | 1405 1.905 | 102 31 | 6,2 6,7° | PP01002 |
| D10x14 / D10x15 | FS1#200 | one piece forged | IEU | Z140 | 1,66 42,2 | 0,217 5,5 | 10 3.048 | 1,890 48,0 | 0,748 19,0 | 1,996 50,7 | 1405 1.905 | 102 31 | 12,2 11,2° | PP01005 |
| D16X20A / D16X22 SERIES II / D20X22 S3 | FS1#250 | one piece forged | IEU | Z140 | 1,90 48,3 | 0,236 6,0 | 10 3.048 | 2,126 54,0 | 0,748 19,0 | 2,500 63,5 | 2043 2.770 | 117 36 | 10,2 9,8° | PP17002 |
| D20x22 / D20X22 SERIES II / D20X22 S3 / D23X30 S3 | FS1#400 | one piece forged | IEU | Z140 | 2,06 52,4 | 0,256 6,5 | 10 3.048 | 2,252 57,2 | 0,874 22,2 | 2,500 63,5 | 2408 3.265 | 127 39 | 9,8 9,0° | PP16001 |
| D23X30 S3 / D24X40 / D24X40A / D24X40 SERIES II / D24X40 S3 | FS1#600 | one piece forged | IEU | Z140 | 2,38 60,3 | 0,280 7,1 | 10 3.048 | 2,638 67,0 | 0,875 22,2 | 2,500 63,5 | 4381 5.940 | 146 44 | 9,3 7,9° | PP04023 |
| D33x44 / D36x50 / D36x50 Series II | FS2#602 | one piece forged | IEU | Z140 | 2,38 60,3 | 0,295 7,5 | 10 3.048 | 2,756 70,0 | 1,181 30,0 | 2,874 73,0 | 4116 5.580 | 146 44 | 9,3 7,9° | PP04015 |
| D33x44 / D36x50 / D36x50 Series II | FS2#602 | one piece forged | IEU | Z140 | 2,38 60,3 | 0,295 7,5 | 15 4.572 | 2,756 70,0 | 1,181 30,0 | 2,874 73,0 | 4116 5.580 | 146 44 | 13,8 11,8° | PP04011 |
| D33X44 / D36X50 / D36X50 SERIES II / D40X50 S3 | FS1#650 | one piece forged | IEU | Z140 | 2,38 60,3 | 0,315 8,0 | 10 3.048 | 2,764 70,2 | 1,000 25,4 | 2,500 63,5 | 5056 6.855 | 146 44 | 9,3 7,9° | PP04024 |
| D33x44 / D36x50 / D36x50 Series II | FS1#650 | one piece forged | IEU | Z140 | 2,38 60,3 | 0,315 8,0 | 15 4.572 | 2,764 70,2 | 0,874 22,2 | 2,500 63,5 | 5310 7.200 | 146 44 | 13,8 11,8° | PP04027 |
| D36X50 / D36X50 SERIES II / D40X55 S3 | FS1#700 | one piece forged | IEU | Z140 | 2,63 66,7 | 0,415 10,5 | 10 3.048 | 3,110 79,0 | 1,102 28,0 | 3,000 76,2 | 7044 9.550 | 165 50 | 10,4 7,0° | PP05005 |
| D36X50 / D36X50 SERIES II / D40X55 S3 | FS1#700 | one piece forged | IEU | Z140 | 2,63 66,7 | 0,415 10,5 | 15 4.572 | 3,110 79,0 | 1,102 28,0 | 3,000 76,2 | 7044 9.550 | 165 50 | 10,4 7° | PP05006 |
| D50x100 / Uni60x70 | FS1#900 | one piece forged | IEU | Z140 | 2,88 73,0 | 0,374 9,5 | 10 3.048 | 3,250 82,6 | 1,181 30,0 | 3,500 88,9 | 7457 10.110 | 177 54 | 9,8 6,5° | PP06006 |
| D50X100 / D50X100a / D60x90 | FS1#900 | one piece forged | IEU | Z140 | 2,88 73,0 | 0,386 9,8 | 15 4.572 | 3,250 82,6 | 1,181 30,0 | 3,500 88,9 | 7457 10.110 | 177 54 | 8,7 9,7° | PP05007 |
| D50X100 / D80x100 Series II / D60x90 | FS1#800 | one piece forged | IEU | Z140 | 3,50 88,9 | 0,374 9,5 | 15 4.572 | 3,622 92,0 | 1,417 36,0 | 3,500 88,9 | 9680 13.125 | 215 66 | 7,5 8,0° | PP09003 |
| D100x120 | FS2#802 | one piece forged | IEU | Z140 | 3,50 88,9 | 0,394 10,0 | 20 6.096 | 4,134 105,0 | 2,244 57,0 | 3,602 91,5 | 11753 15.935 | 215 66 | 11,2 10,7° | PP09001 |
| D100x120 Series / II / D130X150 / D60x90 / D60x90 S3 / D100x140 / D100x140 s3 | FS1#1000 | one piece forged | IEU | Z140 | 3,50 88,9 | 0,472 12,0 | 15 4.572 | 4,331 110,0 | 2,244 57,0 | 3,500 88,9 | 15647 21.215 | 215 66 | 13,2 10,6° | PP09018 |
| D100x120 Series / II / D130X150 / D60x90 / D60x90 S3 / D100x140 / D100x140 s3 | FS1#1000 | one piece forged | IEU | Z140 | 3,50 88,9 | 0,472 12,0 | 20 6.096 | 4,331 110,0 | 2,244 57,0 | 3,500 88,9 | 15647 21.215 | 215 66 | 10,2 10,6° | PP09017 |

*Data subject to change. We do not take any liability for printing errors and/or mistakes. Other sizes and connection types on request, INCOTERMS 2010, MOQ 20pcs
Validity December 31-2022

